

Geometrijske karakteristike B500B armature prema SRPS EN 10080

∅	Površina poprečnog preseka za n komada															Težina
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
[mm]	[cm ²]															[kg/m]
6	0.28	0.57	0.85	1.13	1.41	1.70	1.98	2.26	2.54	2.83	3.11	3.39	3.68	3.96	4.24	0.222
8	0.50	1.01	1.51	2.01	2.51	3.02	3.52	4.02	4.52	5.03	5.53	6.03	6.53	7.04	7.54	0.395
10	0.79	1.57	2.36	3.14	3.93	4.71	5.50	6.28	7.07	7.85	8.64	9.42	10.21	11.00	11.78	0.617
12	1.13	2.26	3.39	4.52	5.65	6.79	7.92	9.05	10.18	11.31	12.44	13.57	14.70	15.83	16.96	0.888
14	1.54	3.08	4.62	6.16	7.70	9.24	10.78	12.32	13.85	15.39	16.93	18.47	20.01	21.55	23.09	1.210
16	2.01	4.02	6.03	8.04	10.05	12.06	14.07	16.08	18.10	20.11	22.12	24.13	26.14	28.15	30.16	1.580
20	3.14	6.28	9.42	12.57	15.71	18.85	21.99	25.13	28.27	31.42	34.56	37.70	40.84	43.98	47.12	2.470
25	4.91	9.82	14.73	19.63	24.54	29.45	34.36	39.27	44.18	49.09	54.00	58.90	63.81	68.72	73.63	3.850
28	6.16	12.32	18.47	24.63	30.79	36.95	43.10	49.26	55.42	61.58	67.73	73.89	80.05	86.21	92.36	4.830
32	8.04	16.08	24.13	32.17	40.21	48.25	56.30	64.34	72.38	80.42	88.47	96.51	104.55	112.59	120.64	6.310
40	12.57	25.13	37.70	50.27	62.83	75.40	87.96	100.53	113.10	125.66	138.23	150.80	163.36	175.93	188.50	9.860
50	19.63	39.27	58.90	78.54	98.17	117.81	137.44	157.08	176.71	196.35	215.98	235.62	255.25	274.89	294.52	15.400