

Nosivost eksera [N]

Ekser d/l	Najmanja deb- ljina drveta za meku građu "a"		Dubina zabija- nja eksera s <sup>2)</sup>		Nosivost jednosečnih eksera		
	A	B	C	D	meka građa		tvrdi dr- vo (samo bušeni ek- seri)
	(mm)	(mm)	(mm)	(mm)	A	B	
22/45	24	24	27	18	200	250	300
22/50	20 <sup>1)</sup>	20 <sup>1)</sup>					
25/55	24	24	30	20	250	310	375
25/60	20 <sup>1)</sup>	20 <sup>1)</sup>					
28/65	24	24	34	23	300	375	450
	20 <sup>1)</sup>	20 <sup>1)</sup>					
31/65	24	24					
31/70	20 <sup>1)</sup>	20 <sup>1)</sup>	38	25	375	480	560
31/80							
34/90	24	24	41	27	430	540	650
	22 <sup>1)</sup>	22 <sup>1)</sup>					
38/100	24	24	46	30	525	650	780
42/110	26	26	51	34	625	775	930
46/130	30	28	56	37	725	905	1090
55/140	40	35	66	34	975	1220	1460
55/160							
60/180	50	35	72	48	1120	1400	1680
70/210	60	45	84	56	1450	1800	2170
75/230	70	45	90	60	1600	2000	2400
80/260	75	50	96	64	1780	2220	2670
90/130	90	55	108	72	2130	2660	3200

1) važi samo za oplata; 2) za punu nosivost;

A - zabijeni ekseri; C - jednosečni ekseri;

B - bušeni ekseri; D - višesečni ekseri;